

COMPUTATIONAL FLUID DYNAMICS
STUDY OF AIR POLLUTANT DISPERSION
AROUND KUANTAN

NORLIYANA BINTI ERAIN

MASTER OF SCIENCE

UNIVERSITI MALAYSIA PAHANG



SUPERVISOR'S DECLARATION

We hereby declare that we have checked this thesis and in our opinion, this thesis is adequate in terms of scope and quality for the award of the degree of Master of Science.

(Supervisor's Signature)

Full Name : DR. JOLIUS GIMBUN
Position : ASSOCIATE PROFESSOR
Date :

(Co-supervisor's Signature)

Full Name : EN NORAM IRWAN BIN RAMLI
Position : LECTURER
Date



STUDENT'S DECLARATION

I hereby declare that the work in this thesis is based on my original work except for quotations and citations which have been duly acknowledged. I also declare that it has not been previously or concurrently submitted for any other degree at Universiti Malaysia Pahang or any other institutions.

(Student's Signature)

Full Name : NORLIYANA BINTI ERAIN

ID Number : MKC15004

Date :

COMPUTATIONAL FLUID DYNAMICS STUDY OF AIR POLLUTANT
DISPERSION AROUND KUANTAN

NORLIYANA BINTI ERAIN

Thesis submitted in fulfilment of the requirements
for the award of the degree of
Master of Science

Faculty of Chemical & Natural Resources Engineering
UNIVERSITI MALAYSIA PAHANG

AUGUST 2019

ACKNOWLEDGEMENTS

First and foremost, I want to thank my supervisor Assoc. Prof. Dr. Jolius Gimbun on his brilliant ideas in computational fluid dynamics study and endless time during my first step doing this research till the end. His continuous support encourages me to finish this research. Secondly, I also want to show my gratitude to my co-supervisor En Noram Irwan bin Ramli for his impressive ideas in topographical design and research writing.

I am also heartily thankful to Ministry of Higher Education Malaysia for the MyBrain15 scholarship towards the end of my study. Also, I acknowledge financial support from UMP through grant RDU150314. Besides that, thank you so much to the lectures and members of staff of Centre of Excellence for Advanced Research in Fluid Flow (CARIFF) and Faculty of Chemical and Natural Resource Engineering (FKKSA), UMP for their help and continuity support either mentally or physically. I really want to show my appreciation to my friend, Law Woon Phui who helps me in finishing this research. She never gives up and her patience also encourages me to finish this research no matter what.

Last but not least, my special thanks goes to my beloved husband, parents and family members for their full support and encouragement to complete this study.

ABSTRAK

Pencemar udara seperti klorin berbahaya kepada benda hidup, alam sekitar dan struktur bangunan apabila ia terkumpul di udara dalam kepekatan yang cukup tinggi. Pendedahan kepada gas klorin boleh menyebabkan kesan akut atau kronik bergantung kepada kepekataannya. Di Malaysia, kawasan perindustrian Gebeng merupakan salah satu kawasan perindustrian terbesar yang terdiri daripada pelbagai kilang pemprosesan seperti petrokimia dan kilang polimer di mana klorin biasanya digunakan dalam petrokimia dan polimer seperti Polyplastics Asia Pacific, Lynas, Petronas-MTBE dan Kaneka Malaysia. Oleh sebab itu, terdapat potensi yang tinggi untuk pembebasan tidak sengaja klorin di kawasan yang dipilih itu dan juga adalah sebab utama dalam memilih klorin sebagai bahan pencemar. Penyebaran pencemar udara dipengaruhi oleh keadaan cuaca dan topografi. Pengukuran dalam bidang eksperimen mempunyai batasan untuk memberikan maklumat terperinci terhadap aliran udara di kawasan kompleks dan oleh itu *computational fluid dynamics* (CFD) digunakan untuk memberikan maklumat yang komprehensif mengenai pengangkutan spesies dan pergolakan pada masa yang sama. Untuk memastikan ketepatan aliran udara pada model CFD, ia mesti disahkan sebelum ia digunakan secara rutin. Jadi, salah satu objektif kajian ini adalah untuk mengkaji aliran angin melalui model yang berskala kecil dengan menggunakan pengukuran *particle image velocimetry* (PIV) dan membandingkannya dengan simulasi CFD. Untuk mencapai objektif ini, parameter seperti kelajuan angin dan arah dikumpulkan dan akan digunakan untuk mendapatkan keputusan dengan menggunakan CFD sebagai alat simulasi. Angin timur biasa dengan kelajuan angin 1.78 m/s digunakan. Aliran perolakan telah dimodelkan dengan menggunakan model *scale-adaptive simulation* (SAS). Model ini telah disahkan dengan pengukuran PIV pada model topografi skala kecil. Ramalan CFD menunjukkan persetujuan yang baik dengan sisihan antara 1.5 hingga 2.6 % daripada pengukuran PIV itu. Oleh itu, model ini boleh digunakan untuk menilai kesan yang menggabungkan permukaan rupa bumi, arah angin dan kelajuan pada penyebaran pencemaran di sekitar kawasan perindustrian Gebeng. Hasil kajian mendapati bahawa kawasan kediaman R1 (Kampung Baru Gebeng, Tanjung Rhu, Kampung Sungai Ular, Kampung Darat Sungai Ular dan Kampung Baging) dan R2 (Kampung Selamat, Kampung Berahi, Kampung Balok, Kampung Seberang Balok, Kampung Balok Baru dan Kampung Balok Perdana) akan terjejas apabila kebocoran klorin berlaku pada bulan Jun hingga September dan November hingga Jan. Pelepasan yang tidak disengajakan gas klorin ini mungkin telah membawa kepada hal kecemasan. Oleh itu, ia juga penting untuk membangunkan plan pemindahan keselamatan yang sesuai sekiranya berlaku kemalangan kebocoran klorin. Laluan dan pusat pemindahan keselamatan yang sesuai adalah dicadangkan untuk kes apabila kawasan perumahan R1 dan R2 terjejas.

ABSTRACT

Air pollutant like the chlorine is harmful to living things, environment and building structures when it accumulates in the air in sufficiently high concentration. Exposure to chlorine gas can cause acute or chronic effects depending on its concentration. In Malaysia, Gebeng industrial area is one of the largest industrial area that consists of various processing plant such as petrochemical and polymer plant where the chlorine is commonly used in the petrochemical and polymer plants such as Polyplastics Asia Pacific, Lynas, Petronas-MTBE and Kaneka Malaysia. So, there are high potential to accidental release of chlorine in the selected area thus as the main reason on choosing the chlorine as pollutant. Air pollutant dispersion is significantly affected by the meteorological and topographical conditions. The field experiment measurement has the limitations to provide detail information of air flow on complex terrain and hence computational fluid dynamics (CFD) techniques is applied to provide the comprehensive information on the species transport and turbulence simultaneously. To ensure the accuracy of the air flow on CFD model, it must be validated before it routinely used. So, one of the objectives for this study is to model the wind flows past a scaled-down model using particle image velocimetry (PIV) measurement and compare with the CFD simulation. To achieve this objective, parameter such as wind speeds and directions was collected and will be used to obtain the results by using CFD as a simulation tools. The typical eastern wind with wind speed 1.78 m/s is used. The turbulence flow was modelled using scale-adaptive simulation (SAS) turbulence model. The model was validated with the PIV measurement on the scale down topography model. The CFD prediction showed good agreement with the error ranging 1.5 to 2.6% from the PIV measurement. Hence, the model can be used to evaluate the combine effect of surface terrain, wind direction and speed on the pollution dispersion around Gebeng industrial area. It was found that the residential area R1 (Kampung Baru Gebeng, Tanjung Rhu, Kampung Sungai Ular, Kampung Darat Sungai Ular and Kampung Baging) and R2 (Kampung Selamat, Kampung Berahi, Kampung Balok, Kampung Seberang Balok Kampung Balok Baru and Kampung Balok Perdana) are affected when the chlorine leakage occurs during June to September and November to January, respectively. Accidental release of this chlorine gas may have led to the emergencies. Hence, it is also important to develop a suitable safety evacuation plan in the event accidental chlorine leak. Suitable safety evacuation route and points is proposed for the case when the residential area R1 and R2 are affected.

TABLE OF CONTENT

DECLARATION	
TITLE PAGE	
ACKNOWLEDGEMENTS	ii
ABSTRAK	iii
ABSTRACT	iv
TABLE OF CONTENT	v
LIST OF TABLES	viii
LIST OF FIGURES	ix
LIST OF SYMBOLS	x
LIST OF ABBREVIATIONS	xii
 CHAPTER 1 INTRODUCTION	 1
1.1 Background of Study	1
1.2 Problem Statement	5
1.3 Objectives of Study	6
1.4 Scopes of Study	6
1.5 Contribution of this Work	7
1.6 Structure of Thesis	8
 CHAPTER 2 LITERATURE REVIEW	 9
2.1 Overview	9
2.2 Air Pollution Phenomenon	9
2.2.1 Factors Affecting Air Pollutant Dispersion	14

2.3	Application of CFD on Topographical Modelling	15
2.3.1	Application of CFD on Air Pollutant Dispersion	17
2.4	Turbulence Modelling	20
2.5	Measurement Techniques in Topographical Modelling	23
2.6	Summary	26
CHAPTER 3 METHODOLOGY		27
3.1	Introduction	27
3.2	Experimental Measurement	29
3.2.1	Topography and environmental conditions of the study area	29
3.2.2	Scaled-down Model Creation	35
3.2.3	Experimental Rig	35
3.3	Numerical Approach	36
3.3.1	Topographical Modelling	36
3.3.2	Meshing	37
3.3.3	Turbulence Modelling	38
3.3.4	Species Transport Modelling	41
3.3.5	Simulation Setup	42
CHAPTER 4 RESULTS AND DISCUSSION		44
4.1	Introduction	44
4.2	Validation of Velocity Profile	44
4.3	Prediction of Chlorine Gas Dispersion around Gebeng Industrial Area	46
4.3.1	Effect of wind speed	47
4.3.2	Effect of wind direction	48
4.3.3	Effect of surface terrain	54

4.4	Safety Evacuation Route	54
CHAPTER 5 CONCLUSION AND RECOMMENDATION		59
5.1	Conclusion	59
5.2	Recommendation	60
REFERENCES		62
APPENDIX A PIV MEASUREMENT SETUP		70
LIST OF PUBLICATIONS		71

LIST OF TABLES

Table 2.1	Health hazard information for different chlorine concentration	11
Table 2.2	Validations acceptable on topographical modelling	17
Table 2.3	Previous study on air pollutant dispersion in industrial sector	20
Table 2.4	Previous study on the turbulence modelling	22
Table 2.5	Measurement Techniques in previous studies	25
Table 3.1	Mean wind speed and direction in each month of 2014	33
Table 4.1	Duration for the chlorine plume to reach residential area in each month of 2014 at different wind speed and wind direction (Note: (a) is mean wind speed and (b) is high wind speed)	48
Table 4.2	Potential affected area and proposed evacuation point in the event accidental chlorine leaks in different seasonal monsoon in 2014	58

LIST OF FIGURES

Figure 2.1	Maximization of the wind velocity above the top of a hill	15
Figure 2.2	Dispersion of a large chlorine release in a complex terrain	18
Figure 2.3	Contour plot of ground level chlorine mass fraction ($\times 10^6$) a) 15, b) 30 and c) 45 minutes after release at 08.00 hours	19
Figure 3.1	Flow chart for the research methodology	28
Figure 3.2	Study area in Gebeng Industrial Estate	30
Figure 3.3	Windrose for Gebeng on January until June 2014	31
Figure 3.4	Windrose for Gebeng on July until December 2014	32
Figure 3.5	Wind direction distribution in % for Kuantan	34
Figure 3.6	Parts of scaled-down model from (a) Sightline maps and (b) printed 3D topography model	35
Figure 3.7	Schematic diagram of PIV measurement setup	36
Figure 3.8	Model creation of (a) contour map in SketchUp, (b) drape surface in Rhinoceros and (c) real solid surface in Rhinoceros	37
Figure 3.9	Surface mesh of Gebeng industrial area (Note: H1, H2 and H3 represent the hills and S1 and S2 represent the source of leakage).	38
Figure 4.1	Vector plot for air flow past Bukit Pengorak hill	45
Figure 4.2	Comparison of CFD and PIV data for, A) u^* along x^* and B) u^* along z^*	46
Figure 4.3	Air pollutant from points S1 and S2 dispersed by eastern wind, 1.3 m/s (a and b) and 8.4 m/s (c and d) on October.	47
Figure 4.4	Chlorine plume disperse by mean wind speed from leak source a) S1 and b) S2 on the month of A) February, B) March, C) April, D) May, E) October.	49
Figure 4.5	Chlorine plume disperse by mean wind speed from leak source a) S1 and b) S2 on the month of A) June, B) July, C) August, D) September.	51
Figure 4.6	Chlorine plume disperse by mean wind speed from leak source a) S1 and b) S2 on the month of A) November, B) December, C) January.	53
Figure 4.7	Vector plot for chlorine plume disperse from leak source A) S1, B) S2 towards hill H3 by eastern wind.	54
Figure 4.8	Proposed safety evacuation route if residential area R1 is affected from source A) S1 and B) S2.	56
Figure 4.9	Proposed safety evacuation route if residential area R2 is affected from leak sources A) S1 and B) S2.	57

LIST OF SYMBOLS

α	Speed of sound (m/s)
C_μ	Coefficient of turbulent viscosity
$C_{1\epsilon}$	Constant of production rate
$C_{2\epsilon}$	Constant of destruction rate
$C_{3\epsilon}$	Coefficient of production rate
D_m	Diffusion coefficient (m ² /s)
D_t	Turbulent diffusion coefficient (m ² /s)
G_k	Production term of turbulence kinetic energy
G_b	Production term due to turbulence buoyancy
g_i	Gravitational vector
\vec{J}	Diffusion flux
k	Turbulent kinetic energy (m ² /s ²)
L	Length scale in SAS model
L_{vK}	Von Karman length scale
M_t	Turbulent Mach number
P_k	Production rate term in SAS model
Pr_t	Turbulent Prandtl number
R	Source term by chemical reaction
S	Mean strain rate
S_i	Additional term
T	Temperature (K)
\vec{u}	Velocity (m/s)
Y	Mass fraction
Y_M	Dilatation dissipation term
β	Thermal expansion coefficient
μ_t	Turbulent viscosity (kg/m.s)
ρ	Density (kg/m ³)
μ	Viscosity of fluid (kg/m.s)
σ_ϵ	Turbulent Prandtl number for turbulent dissipation rate
σ_k	Turbulent Prandtl-Schmidt number for turbulent kinetic energy
σ_Φ	Turbulent Prandtl number for SAS model

ε	Turbulent dissipation rate (m^2/s^3)
Φ	Coefficient
γ	Ratio of specific heat
$\zeta_1, \zeta_2, \zeta_3$	Constant

LIST OF ABBREVIATIONS

AABL	Adiabatic atmospheric boundary layer
ABS	Acrylonitrile butadiene styrene
AP	Aspiration probe
CCD	Charged-couple device
CFD	Computational fluid dynamics
FFID	Fast flame ionisation detector
GIE	Gebeng Industrial Estate
IBM	Immersed Boundary Method
LDA	Laser Doppler anemometry
LDV	Laser Doppler velocimetry
LES	Large eddy simulation
LS-PIV	Large scale-particle image velocimetry
LST	Light scattering technique
MADM	Module for the atmospheric dispersion modelling
MIC	Methyl isocyanate
MIDA	Malaysian Investment Development Authority
MSL	Mean sea level
MTBE	Methyl tert-butyl ethylene
PIV	Particle image velocimetry
PPM	Parts per million
PTV	Particle tracking velocimetry
RANS	Reynolds-averaged Navier-Stokes
RKE	Realizable k- ϵ
RNG	Renormalized k- ϵ
RSM	Reynolds stress model
SAS	Scale adaptive simulation
SKE	Standard k- ϵ
TIN	Triangulated irregular network
URANS	Unsteady Reynolds-averaged Navier-Stokes

REFERENCES

- Abdullah, M. Z., Ismail, A., & Mahammad, N. I. (2014). Statistical analysis of heavy metal concentration in moss and soil as indicator of industrial pollution. *International Journal of Science, Environment and Technology*, 3(3), 762–775.
- Abdullah, M. Z., Azhar, N. F., & Abdul Kadir, S. M. (2015). Deposition Of Heavy Metals In Soil And Higher Plant Related To Rare-Earth Processing Activities. *Jr. of Industrial Pollution Control*, 31(2), 315–321.
- Alhassan, M., & Jimoh, A. (2006). Modeling and Simulation of Air Pollutant Dispartion a Case Study of an Industrial Area in Nigeria. *Leonardo Journal of Sciences*, 9(9), 137–148.
- Andersson, B., Andersson, R., Hakansson, L., Mortensen, M., Sudiyo, R., & Wachem, B. V. (2011). Computational Fluid Dynamics for Engineers. *Cambridge University Press*. New York.
- Assimakopoulos, V. D., ApSimon, H. M., & Moussiopoulos, N. (2003). A numerical study of atmospheric pollutant dispersion in different two-dimensional street canyon configurations. *Atmospheric Environment*, 37(29), 4037–4049.
- Austin, A. (2005, May). Preventing chlorine gas accidents. Retrieved from <http://ohsoline.com/>
- Baik, J. J. & Kim, J. J. (1999) A numerical study of flow and pollutant dispersion characteristics in urban street canyons. *Journal of Applied Meteorology*, 38, 1576–1589.
- Beyers, M., & Waechter, B. (2008). Modeling transient snowdrift development around complex three-dimensional structures. *Journal of Wind Engineering and Industrial Aerodynamics*, 96, 1603–1615.
- Blocken, B., Stathopoulos, T., & Carmeliet, J. (2007). CFD simulation of the atmospheric boundary layer: wall function problems. *Atmospheric Environment*, 41(2), 238–252.
- Balogh, M., Parente, A., & Benocci, C. (2012). RANS simulation of ABL flow over complex terrains applying an Enhanced k- ϵ model and wall function formulation: Implementation and comparison for fluent and OpenFOAM. *Journal of Wind Engineering and Industrial Aerodynamics*, 104–106, 360–368.
- Borchers, O., Busch, C., Sokolichin, A. and Eigenberger, G. (1999) "Applicability of the standard k- ϵ turbulence model to the dynamic simulation of bubble columns. Part II: Comparison of detailed experiments and flow simulations", *Chem. Eng. Sci.*, 54, pp.5927-5935

- Cai, X. M., Barlow, J. F., & Belcher, S. E. (2008). Dispersion and transfer of passive scalars in and above street canyons-Large-eddy simulations. *Atmospheric Environment*, 42(23), 5885–5895.
- Cai, P., Nie, W., Chen, D., Yang, S., & Liu, Z. (2019). Effect of air flowrate on pollutant dispersion pattern of coal dust particles at fully mechanized mining face based on numerical simulation. *Fuel*, 239 (May 2018), 623–635.
- Calabrese, E. J., & Kenyon, E. M. (1991). Air toxics and risk assessment.
- Chan, T. L., Dong, G., Leung, C. W., Cheung, C. S., & Hung, W. T. (2002). Validation of a two-dimensional pollutant dispersion model in an isolated street canyon. *Atmospheric Environment*, 36(5), 861–872.
- Chow, F. K., & Street, R. L. (2009). Evaluation of Turbulence Closure Models for Large-Eddy Simulation over Complex Terrain: Flow over Askervein Hill. *Journal of Applied Meteorology and Climatology*, 48, 1050–1065.
- Corsmeier, U., Behrendt, R., Drobinski, Ph., Kottmeier, Ch. (2005). The mistral and its effect on air pollution transport and vertical mixing. *Atmospheric Research*, 74, 275-302.
- De la Torre, A., Pessano, H., Hierro, R., Santos, J. R., Llamedo, P., & Alexander, P. (2015). The influence of topography on vertical velocity of air in relation to severe storms near the Southern Andes Mountains. *Atmospheric Research*, 156, 91–101.
- Deen, N. G., Hjertager, B. H., & Solberg, T. (2000). Comparison of PIV and LDA Measurement Methods Applied to the Gas-Liquid Flow in a Bubble Column. *10th Int. Symp. on Appl. of Laser Techniques to Fluid Mech*, Lisbon, Portugal: 10-13 July.
- Deng, Y., Hu, H., Yu, B., Sun, D., Hou, L., & Liang, Y. (2018). A method for simulating the release of natural gas from the rupture of high-pressure pipelines in any terrain. *Journal of Hazardous Materials*, 342, 418–428.
- Dharmawan and Hanna. (2007). Computational Fluid Dynamic (CFD) modelling of toxic gas dispersion in the vicinity of complex buildings, structures, and topography. *ICHEME Symposium Series No.153*.
- Di Sabatino, S., Buccolieri, R., Pulvirenti, B., & Britter, R. E. (2008). Flow and pollutant dispersion in street canyons using FLUENT and ADMS-Urban. *Environmental Modeling and Assessment*, 13(3), 369–381.
- Diebold, M., Higgins, C., Fang, J., Bechmann, A., & Parlange, M. B. (2013). Flow over Hills: A Large-Eddy Simulation of the Bolund Case. *Boundary-Layer Meteorology*, 148(1), 177–194.
- Dominick, D., Latif, M. T., Juahir, H., Aris, A. Z., & Zain, S. M. (2013). An assessment on influence of meteorological factors on PM10 and NO₂ at selected stations in Malaysia. *Sustainable Environment Research*, 22(5), 305–315.

- EPA (Environmental Protection Agency), U. S. (1999). Chlorine gas. Prevention, Pesticides and Toxic Substances.
- Fesquet, C., Drobinski, P., Barthlott, C., & Dubos, T. (2009). Impact of terrain heterogeneity on near-surface turbulence structure. *Atmospheric Research*, 94(2), 254–269.
- Finardi, S., & Morselli, M. G. (1997). Wind flow models over complex terrain for dispersion calculations. *Working Group*, (May 1997), 1–51.
- Gilham, S., Deaves, D. M., & Woodburn, P. (2000). Mitigation of dense gas releases within buildings: Validation of CFD modelling. *Journal of Hazardous Materials*, 71(1–3), 193–218.
- Goh, J. (2017, July). Gas leak at KB Water Dept. Retrieved from <http://www.dailyexpress.com.my/>
- Gosman, A. D. (1999). Developments in CFD for industrial and environmental applications in wind engineering. *Journal of Wind Engineering and Industrial Aerodynamics*, 81, 21–39.
- Gousseau, P., Blocken, B., Stathopoulos, T., & van Heijst, G. J. F. (2011). CFD simulation of near-field pollutant dispersion on a high-resolution grid: A case study by LES and RANS for a building group in downtown Montreal. *Atmospheric Environment*, 45(2), 428–438.
- Grigoras, G., Cuculeanu, V., Ene, G., Mocioaca, G., & Deneanu, A. (2012). Air pollution dispersion modeling in a polluted industrial area of complex terrain from Romania. *Romanian Reports in Physics*, 64(1), 173–186.
- Ha, T., Lee, I. Bok, Kwon, K. Seok, & Lee, S. J. (2018). Development of a micro-scale CFD model to predict wind environment on mountainous terrain. *Computers and Electronics in Agriculture*, 149(November 2017), 110–120.
- HHS (Department of Health and Human Services), U. S. (1993). Hazardous Substances Data Bank (HSDB, online database). National Toxicology Information Program, National Library of Medicine, Bethesda, M. D.
- Holmes, N. S., & Morawska, L. (2006). A review of dispersion modelling and its application to the dispersion of particles: an overview of different dispersion models available. *Atmospheric Environment*, 40, 5902–5928.
- Hong, S., Lee, I., Hwang, H., Seo, I., Bitog, J., Kwon, K., Song, J., Moon, O., Kim, K., Ko, H. (2011). CFD modelling of livestock odour dispersion over complex terrain, part I: Topographical modelling. *Biosystems Engineering*, 108(3), 253–264.
- Hong, S., Lee, I., Hwang, H., Seo, I., Bitog, J., Kwon, K., Song, J., Moon, O., Kim, K., Ko, H. (2011). CFD modelling of livestock odour dispersion over complex terrain, part II: Dispersion modelling. *Biosystems Engineering*, 108(3), 265–279.

- Hsieh, K.-J., Lien, F.-S. & Yee, E. (2007) Numerical modeling of passive scalar dispersion in an urban canopy layer. *Journal of Wind Engineering and Industrial Aerodynamics*, 95, 1611-1636.
- Huang, H., Akutsu, Y., Arai, M., & Tamura, M. (2000). A two-dimensional air quality model in an urban street canyon: Evaluation and sensitivity analysis. *Atmospheric Environment*, 34(5), 689–698.
- Hyun, B.-S., Balachandar, R., Yu, K., & Patel, V. C. (2003). Piv/Ldv Measurements of Mean Velocity and Turbulence in a Complex Open Channel Flow. (424).
- Ingram, D. M., Causon, D. M., & Mingham, C. G. (2003). Developments in Cartesian cut cell methods. *Mathematics and Computers in Simulation*, 61, 561–572.
- Institution of Occupational Safety and Health (IOSH), 2008. Chlorine equipment. In: Material Safety Data Sheets SDS-E-002, 0005, <http://www.iosh.gov.tw/>
- Jadidi, M., Bazdidi-Tehrani, F., & Kiamansouri, M. (2018). Scale-adaptive simulation of unsteady flow and dispersion around a model building: spectral and POD analyses. *Journal of Building Performance Simulation*, 11(2), 241–260.
- Jayamurugan, R., Kumaravel, B., Palanivelraja, S., & Chockalingam, M. P. (2013). Influence of Temperature, Relative Humidity and Seasonal Variability on Ambient Air Quality in a Coastal Urban Area. *International Journal of Atmospheric Sciences*, 2013, 1–7.
- Kamada, Y., Li, Q., Maeda, T., & Yamada, K. (2019). Wind tunnel experimental investigation of flow field around two-dimensional single hill models. *Renewable Energy*, 136, 1107–1118.
- Katsaprakakis, D. A. & Christakakis, D. G. (2012). Wind Energy. *Comprehensive Renewable Energy*.
- Koh, K. (2017, September). Melaka chlorine gas leak: Residents return home after removal of cylinders from neighborhood. *Nst*. Retrieved from <https://www.nst.com.my/>
- Kumar, P., Singh, S. K., Ngae, P., Feiz, A. A., & Turbelin, G. (2017). Assessment of a CFD model for short-range plume dispersion: Applications to the Fusion Field Trial 2007 (FFT-07) diffusion experiment. *Atmospheric Research*, 197(June), 84–93.
- Laeng, J. (2018). Nine people rushed to hospital for suspected inhalation of poisonous gas. Retrieved from <http://www.theborneopost.com/> (accessed 30 July 2019).
- Launder, B. E., & Spalding, D. B. (1974). The Numerical Computation of Turbulent Flows. *Computer Methods in Applied Mechanics and Engineering*, 3, 269–289.

- Letzel, M. O., Krane, M. & Raasch, S. (2008) High resolution urban large-eddy simulation studies from street canyon to neighbourhood scale. *Atmospheric Environment*, 42, 8770-8784.
- Linfield, K. W., & Mudry, R. G. (2008). Pros and Cons of CFD and Physical Flow Modeling. *Airflow Sciences Corporation*.
- Liu, Y., Chen, D., Kahn, R. A., & He, K. Bin. (2009). Review of the applications of Multiangle Imaging SpectroRadiometer to air quality research. *Science in China, Series D: Earth Sciences*, 52(1), 132–144.
- Liu, Z., & Ishihara, T. (2014). Numerical study of turbulent flow over complex topography by LES model. 1–8.
- Liu, B., Liu, X., Lu, C., Godbole, A., Michal, G., & Tieu, A. K. (2016). Computational fluid dynamics simulation of carbon dioxide dispersion in a complex environment. *Journal of Loss Prevention in the Process Industries*, 40, 419–432.
- Ma, X., Zhong, W., Feng, W., & Li, G. (2017). Modelling of pollutant dispersion with atmospheric instabilities in an industrial park. *Powder Technology*, 314, 577–588.
- Maharani, Y. N., Lee, S., & Lee, Y. (2009). Topographical Effect on Wind Speed over Various Terrains: A Case Study for Korean Peninsula. *The Seventh Asia-Pacific Conference on Wind Engineering, Taipei, Taiwan*.
- Maliska, C. R., Paladino, E. E., Saltara, F., Contessi, B. A., & Ataides, R. (2012). A Comparison of Turbulence Models for the Computation of a Detached Flow around a Square Cylinder.
- McBride, M. A., Reeves, A. B., Vanderheyden, M. D., Lea, C. J., & Zhou, X. X. (2001). Use of advanced techniques to model the dispersion of chlorine in complex terrain. *Process Safety and Environmental Protection*, 79(2), 89–102.
- Michálek, P., & Zacho, D. (2015). Wind tunnel studies of gas dispersion over complex terrain. In *EPJ Web of Conferences* (Vol. 114).
- Malaysian Investment Development Authority (MIDA). (2013). Petrochemical Industry.
- Menter, F. R., & Egorov, Y. (2006). SAS Turbulence Modelling of Technical Flows. *Direct and Large-Eddy Simulation VI*, 687–694.
- Murakami, S. (1990). Numerical simulation of turbulent flowfield around cubic model current status and applications of k- ϵ model and LES. *Journal of Wind Engineering and Industrial Aerodynamics*, 33(1–2), 139–152.
- Murakami, S., Mochida, A. and Hayashi, Y., 1988: Modification of production terms in k- ϵ Model to remove overestimate of k value around windward corner. *10th Wind Engineering Symposium*, 199-204.

- Murena, F., & Mele, B. (2016). Effect of balconies on air quality in deep street canyons. *Atmospheric Pollution Research*, 7(6), 1004–1012.
- Nakiboglu, G., Gorle, C., Horvath, I., Beeck, J. Van, & Blocken, B. (2009). Stack gas dispersion measurements with Large Scale-PIV, Aspiration Probes and Light Scattering Techniques and comparison with CFD. *Atmospheric Environment*, 43, 3396–3406.
- Nosek, S., Janour, Z., Kukacka, L., Jurcakova, K., Kellnerova, R., & Gulikova, E. (2013). Atmospheric dispersion modelling over complex terrain at small scale. *EPJ Web of Conferences*.
- Onianwa, P. C., Ajayi, S. O., Osibanjo, O., & Egunyomi, A. (1986). Accumulation patterns of heavy metals in forest mosses from the south-west region of Nigeria. *Environmental Pollution Series B, Chemical and Physical*, 11(1), 67–78.
- Pilloni, M. T., Schram®, C., & Riethmülle, M. L. (2000). PIV and LDV measurements behind a backward facing step. *Air Pollution VIII*, 633–642.
- Rasouli, A., Hangan, H., & Siddiqui, K. (2009). PIV measurements for a complex topographic terrain. *Journal of Wind Engineering and Industrial Aerodynamics*, 97(5–6), 242–254.
- Riddle, A., Carruthers, D., Sharpe, A., McHugh, C., & Stocker, J. (2004). Comparisons between FLUENT and ADMS for atmospheric dispersion modelling. *Atmospheric Environment*, 38, 1029–1038.
- Rotta, J. C., (1972). *Turbulent Flows (Turbulente Stromungen)*. Teubner-Verlag, Stuttgart.
- Saga, T., Hu, H., Kobayashi, T., Segawa, S., Taniguchi, N., Measuring, F., & Division, I. (1999). A Comparative Study of the PIV and LDV Measurements on a Self-induced Sloshing Flow. *3rd International Workshop on PIV*. Santa Barbara, USA: 16–18 September.
- Salim, S. M., Buccolieri, R., Chan, A., & Di Sabatino, S. (2011). Numerical simulation of atmospheric pollutant dispersion in an urban street canyon: Comparison between RANS and LES. *Journal of Wind Engineering and Industrial Aerodynamics*, 99(2–3), 103–113.
- Sarkar, S., & Balakrishnan, L. (1990). Application of a Reynolds Stress Turbulence Model to the Compressible Shear Layer. In *AIAA journal* (Vol. 29).
- Scargiali, F., Di Rienzo, E., Ciofalo, M., Grisafi, F., & Brucato, A. (2005). Heavy gas dispersion modelling over a topographically complex mesoscale a cfd based approach. *Process Safety and Environmental Protection*, 83(3 B), 242–256.
- Scargiali, F., Grisafi, F., Busciglio, A., & Brucato, A. (2011). Modeling and simulation of dense cloud dispersion in urban areas by means of computational fluid dynamics. *Journal of Hazardous Materials*, 197, 285–293.

- So, E. S. P., Chan, A. T. Y. & Wong, A. Y. T. (2005) Large-eddy simulations of wind flow and pollutant dispersion in a street canyon. *Atmospheric Environment*, 39, 3573-3582.
- Sobahan, M. A., & Islam, M. S. (2015). Integrated Assessment of Heavy Metal Contamination in Sediments from. *Research Journal of Recent Sciences*, 4(11), 26-35.
- Spalart, P. R. (2000). Strategies for turbulence modelling and simulations. *International Journal of Heat and Fluid Flow*, 21(3), 252-263.
- Sudarsan, J. S., Thattai, D., Shah, U. K., & Mitra, A. (2016). Micrometeorological tower observations and their importance in atmospheric modelling and space technology. *Indian Journal of Science and Technology*, 9(42), 1-6.
- Sujaul, I. M., Hossain, M. A., Nasly, M. A., & Sobahan, M. A. (2013). Effect of Industrial Pollution on the Spatial Variation of Surface Water Quality. *American Journal of Environmental Science*, 9(2), 120-129.
- Tamura, Y., & Matsui, M. (2002). - Recent topics in wind engineering focusing on monitoring techniques. In M. Anson, J. M. Ko, & E. S. S. Lam (Eds.), *Advances in Building Technology* (pp. 65-74).
- Teneler, G. (2011). Wind Flow Analysis on a Complex Terrain. *Master of Science Thesis*. Gotland University.
- Tominaga, Y. & Stathopoulos, T. (2010) Numerical simulation of dispersion around an isolated cubic building: Model evaluation of RANS and LES. *Building and Environment*, 45, 2231-2239.
- Tominaga, Y., & Stathopoulos, T. (2011). CFD modeling of pollution dispersion in a street canyon: Comparison between LES and RANS. *Journal of Wind Engineering and Industrial Aerodynamics*, 99(4), 340-348.
- Vladut, A. C., Cosoiu, C. I., Georgescu, A. M., Degeratu, M., & Damian, R. M. (2016). Wind Tunnel and Numerical Modeling of Atmospheric Boundary Layer Flow over Bolund Island. *Energy Procedia*, 85 (November 2015), 603-611.
- Warner P.O. 1976. Analysis of Air Pollutions. John Wiley and Son, New York. 329.
- White, C. W., & Martin, J. G. (2010). Chlorine Gas Inhalation: Human Clinical Evidence of Toxicity and Experience in Animal Models. *Proceedings of the American Thoracic Society*, 7(4), 257-263.
- Xie, X., Huang, H. & Wang, J. (2006). The impact of urban street layout on local atmospheric environment. *Building and Environment*, 41, 1352-1363.
- Yeap, A. (2016, September). Chlorine gas causes scare around plant. Retrieved from <https://www.thestar.com.my/>

- Zaharim, A., Shaharuddin, M., Nor, M. J. M., Karim, O. A., & Sopian, K. (2009). Relationships between airborne particulate matter and meteorological variables using non-decimated wavelet transform. *European Journal of Scientific Research*, 27(2), 308-312.
- Zhang, H., Xu, T., Zong, Y., Tang, H., Liu, X., & Wang, Y. (2015). Influence of Meteorological Conditions on Pollutant Dispersion in Street Canyon. *Procedia Engineering*, 121, 899–905.